

DESIGN OF STRIP FOOTINGS OVER SOIL REINFORCED BY  
RAMMED AGGREGATE PIERS

This Technical Bulletin discusses the design concepts for the structural design of strip footings supported by Rammed Aggregate Pier® (RAP) soil reinforcing elements. Conventional strip footings supported at grade are traditionally designed assuming that the subgrade soils beneath the footings provide uniform support. The installation of RAPs beneath strip footings provides for stiffer support at the pier locations resulting in a non-uniform support condition beneath the strip footing. The design of Rammed Aggregate Pier supported strip footings, therefore, must include considerations for the difference in stiffness profile and contribution of subgrade support beneath the footings.

1. DESIGN OF CONVENTIONAL STRIP FOOTINGS SUPPORTED AT GRADE

The design of shallow strip footings supported by unreinforced soil is typically performed using guidelines published by the American Concrete Institute (ACI-318). The minimum footing width (B) is determined from the uniformly distributed load (w) and allowable bearing pressure (q):

$$B = \frac{w}{q} \quad (1)$$

where w is the distributed footing load in units of force per unit length and q is the allowable soil bearing pressure in units of force per unit area.

Because the applied wall load (w) is coincident with the uniform resisting pressure (q), the footing is not subject to bending moments along its longitudinal axis (Figure 1a).




Figure 1a.  
Strip Footing Supported at Grade

---

## 2. DESIGN OF GRADE BEAMS SUPPORTED BY DEEP FOUNDATIONS

---

Because pile foundations are infinitely stiff compared to the unreinforced soil, the entire wall load is assumed to be resisted by the deep foundations. Typically a grade beam is designed to completely transfer all of the loads to the piles. Figure 1b shows a schematic of a grade beam supported by deep foundations. The load from the superstructure is resisted by shear forces and bending moments by the reinforced grade beam.

The maximum shear,  $V$ , and bending moment,  $M$ , are calculated using the following equations:

$$V_{\max} = \frac{wL}{2} \quad (2)$$

$$M_{\max} = \frac{wL^2}{8} \quad (3)$$

where:

$w$  is the uniformly-distributed load in units of force per unit length and  $L$  is the footing length between piles.




Figure 1b.  
Grade Beam Supported by Pile Foundations

---

## 3. DESIGN OF STRIP FOOTINGS SUPPORTED BY RAPs

---

RAP supported strip footings (Figure 1c) represent an intermediate condition between conventional uniform soil-supported strip footings and pile-supported grade beams. Because the pier-soil stiffness ratio ( $R_s$ ) is often in the range of 5 to 40 (Lawton and Fox 1994, Lawton et al. 1994, Lawton and Merry 2000) and because RAP elements require confinement from the matrix soil, the soil between the elements resists a portion of the applied wall load.

The shear and bending moment that develops within RAP-supported footings may be estimated as:




Figure 1c.  
Strip Footing Supported by RAPs

$$V = \frac{w_{net} L}{2} \quad (4)$$

$$M = \frac{w_{net} L^2}{8} \quad (5)$$

Where  $w_{net}$  is the net wall load applied to the strip footing. The value for  $w_{net}$  may be computed as:

$$w_{net} = w - q_m B \quad (6)$$

where  $q_m$  is the bearing pressure resisted by the matrix soil.

Using equations of statics and the assumption that the strip footing exhibits uniform settlement,  $q_m$  (Lawton and Fox, 1994, Lawton et.al. 1994, Fox and Cowell, 1998, Wissmann, et.al., 2000) may be computed as:

$$q_m = \frac{q}{R_a R_s + R_a + 1} \quad (7)$$

where  $R_a$  is the ratio of the cross-sectional area of the RAP elements to the footprint area of the footing.  $R_a$  is estimated as  $\frac{A_g}{sB}$  where  $s$  is the pier center-to-center spacing and  $B$  is the footing width.  $R_s$  is the ratio of the stiffness of the RAP element to the matrix soil, and  $q$  is the average soil bearing pressure computed as:

$$q = \frac{w}{B} \quad (8)$$

For lightly-loaded strip footings, the area replacement ratio typically varies between 15% and 25%. The net distributed load approach results in a reduction in shear and moment demand on the strip footings. The reduction in shear and moment may be quantified in terms of a reduction factor  $R_d$ , that depends on pier spacing and stiffness ratio. This reduction factor may be used to compute the maximum shear and bending moment exerted on RAP-supported footings with the following expressions:

$$V_{max} = \frac{w_{net} L}{2} [R_d] \quad (9)$$

$$M_{max} = \frac{w_{net} L^2}{8} [R_d] \quad (10)$$

$$R_d = \left[ 1 - \frac{(s-d)B}{R_s A_g + A_s} \right] \quad (11)$$

where

$d$  = RAP diameter

$A_s$  = area of matrix soil beneath the strip footing and between the RAP elements.

## CONCLUSIONS

Strip footings supported by Rammed Aggregate Pier soil reinforcing elements may be designed by taking into account support contribution from the reinforced soil between the piers. The approach introduces shear and moment reduction factors depending on the pier

spacing and stiffness ratio to provide a more efficient design for steel reinforcement and footing thickness than designing the strip footing as a grade beam spanning between the piers.

## AUTHORS

Kord J. Wissmann, Ph.D., P.E., President/Chief Engineer, Geopier Foundation Company, Inc.  
Rimas Veitas, P.E., President, Helical Drilling  
Jorge R. Parra, Ph.D., P.E., Lead Engineer, Latin America, Geopier Foundation Company, Inc.

## REFERENCES

American Concrete Institute (ACI – 318)

Lawton, E. C. and Fox, N. S. (1994). "Settlement of Structures Supported on Marginal or Inadequate Soils Stiffened with Short Aggregate Piers." Proceedings, Vertical and Horizontal Deformations of Foundations and Embankments. College Station, TX.

Lawton, E. C., Fox, N. S. and Handy, R. L. (1994). "Control of Settlement and Uplift of Structures Using Short Aggregate Piers." Proceedings, IN-SITU Deep Soil Improvements.

Lawton, E., and S. Merry. (2000). "Performance of Geopier® Supported Foundations During Simulated Seismic Tests on Northbound Interstate 15 Bridge Over South Temple, Salt Lake City, Utah." Final Report No. UUCVEEN 00-03. University of Utah.

Geopier Foundation Company, Inc.  
150 Fairview Road, Suite 335  
Mooresville, NC 28117

Telephone: (704) 799.3185 or (800) 371.7470  
Fax: (704) 799.3235

Email: [info@geopier.com](mailto:info@geopier.com)  
[www.geopier.com](http://www.geopier.com)







---

A  **tensar**® Company

Geopier Foundation Company, Inc.

800.371.7470  
[www.geopier.com](http://www.geopier.com)

11\_2007